



PH: (800) 403-0011 / FX: (800)952-8281

LUBENET ENGINE OILS MONOGRADES

PRODUCT SPECIFICATIONS & TECHNICAL DATA

LUBENET ENGINE OILS are formulated to provide optimum performance in modern, low emission diesel engines operating under a wide variety of service conditions. They are blended with premium base stocks and high quality additive to achieve the following benefits: high temperature piston deposit control, foam protection, soot dispersancy and oil thickening control, oxidation inhibition, low temperature sludge protection, corrosion and rust inhibition, valve train wear protection and TBN retention.

LUBENET ENGINE OILS are recommended for use in turbo-charged and naturally aspirated two and four cycle diesel engines. They may also be used in gasoline engines for the “mixed fleet” operator. These motor oils, provide excellent performance in local stop and go routes, on and off highway, farm construction and mining applications.

TYPICAL PROPERTIES	40WT	50WT	10WT	30WT	
Gravity	26.4		29.7	27.3	27.0
Viscosity @ SUS 100F. 1004			225	568	782
Viscosity @ SUS 210F. 95			48	68	82
Viscosity Index		121	108	105	101
CCS Viscosity @-20°C Cp			2500	--	--
CCS Viscosity @-15°C Cp			--	--	--
Pour Point F. +10			-15	0	+5
Total Base No. (ASTM D-2896) 9.3			9.3	9.3	9.3
Sulfated Ash wt. % 1.2			1.2	1.2	1.2
Zinc Wt. % 0.13			0.13	0.13	0.13

The above analyses are typical inspections only and the finished product may vary from batch to batch.