



PH: (718) 417-6464 \* (800) 403-0011 / FX: (718) 628-1262

## LUBENET NON-DETERGENT OILS

### PRODUCT SPECIFICATIONS & TECHNICAL DATA

**LUBENET NON-DETERGENT OILS** are blended from select high V.I. base stocks, containing oxidations, corrosion and, anti-wear inhibitors to protect engines operating under moderate conditions.

#### **PROPERTIES & BENEFITS:**

- Strict viscosity control insures quality products at all times;
- High viscosity index promotes stable lubricating film, at various operating temperatures;
- Low pour point insures quick starts under cold starting conditions;
- Oxidations stability inhibitor fortifies the natural stability of the oil;
- Various grades available in wide range of viscosity.

#### **APPLICATION:**

For light to moderate duty service

#### **TYPICAL ANALYSIS**

	<b>10W</b>	<b>20W</b>	<b>30W</b>	<b>40W</b>	<b>50W</b>
<b>ISO Grade</b>	46	68	100	150	220
<b>Gravity API</b> 27.0	29.0	27.6	26.9	27.0	
<b>Viscosity:</b>					
<b>SUS @ 100° F</b> 1250	230	335	550	850	
<b>SUS @ 210° F</b> 101	49	55	70	82	
<b>Viscosity Index</b>	105	105	105	105	105

<b>Flash Point</b> 475	395	415	435	455
<b>Pour Point</b> +14	-15	-15	-4	+5

The above analyses are typical inspections only and the finished product may vary from batch to batch.